

# PB-Li 12-200

Rev.-Nr.: 2.0 | 2023



# POWER BOOST

high power **battery series**

**LFP** LiFePO<sub>4</sub>  
LITHIUM BATTERY



## ELECTRICAL SPECIFICATIONS

Nominal Voltage	12,8 V
Nominal Capacity	200 Ah
Open Circuit Volt. @ 100%	13,3 V
Energy	2560 Wh
Internal Resistance	≤ 50 mΩ
Self Discharge	<3% / month
Max. Batteries in Series	4

## DISCHARGING

Max. cont. Discharge Current	270 A
Peak Discharge Current	500 A (180 s)
BMS Discharge Cut-Off	800 A (3s)
BMS Cut-Off	10,4 V
Reconnect Voltage	11,6 V

## TEMPERATURES

Discharge Temperature	-20 to +65°C
Charge Temperature	0 to +65 °C
Storage Temperature	0 to +40 °C

## COMMUNICATION

Bluetooth 4.0 with App Android/iOS

## MECHANICAL SPECIFICATIONS

Dimensions (LxWxH)	353 x 350 x 188 mm
Weight	25,3 kg
Terminal Type	M8
Case Material	Metal
Enclosure Protection	IP 56
Cell Type / Chemistry	Prismatic / LiFePO <sub>4</sub>

## CHARGING


Recomm. Charge Current	50 A
Max. Charge Current	210 A
Recomm. Charge Voltage	14,6 V
BMS Voltage Cut-Off	15 V

## COMPLIANCE

Certificates	CE UN38.3 UL1642 & IEC62133
Shipping Classification	UN 3480, Class 9

MEMBER OF SUNLIGHT GROUP  
**A. MÜLLER**  
GmbH

A. Müller GmbH  
Tholeyer Straße 32  
D-66620 Nonnweiler-Primstal  
Mail: info@batterien-mueller.de



gültig ab 01/2023